

Specific energy consumption (SEC) cold	[ kWh/m²a ]	-76.1
Specific energy consumption (SEC) average	[ kWh/m²a ]	-35.7
Specific energy consumption (SEC) warm	[ kWh/m²a ]	-12.5
Declared typology		bidirectional
Type of drive installed (fan)		Variable
Type of heat recovery system		regenerative
Thermal efficiency of heat recovery	[ % ]	75
Maximum flow rate	[ m³/h ]	400
Electric power input of the fan drive at maximum flow rate	[ W ]	168
Sound power level (Lwa)	[ dB(A) ]	46
Reference flow	[ m³/s ]	0.08
Reference pressure difference	[ Pa ]	50
SPI	[ W/(m³/h) ]	0.29
Control factor and control typology		0.85
Declared maximum internal leakage rates	[ % ]	3.00
Declared maximum external leakage rates	[ % ]	2.61
Possition and description of visual filter warning for RVU's		Timer
AEC average	[ kWh ]	260
AEC cold	[ kWh ]	260
AEC warm	[ kWh ]	260
AHS Average	[ kWh/a ]	4220
AHS Cold	[ kWh/a ]	8260
AHS Warm	[ kWh/a ]	1910
Internet address for disassembly instructions		www.salda.it

