

Specific energy consumption (SEC) cold	[ kWh/m <sup>2</sup> a ]	-76.3
Specific energy consumption (SEC) average	[ kWh/m <sup>2</sup> a ]	-35.9
Specific energy consumption (SEC) warm	[ kWh/m <sup>2</sup> a ]	-12.8
Declared typology		bidirectional
Type of drive installed (fan)		Variable
Type of heat recovery system		regenerative
Thermal efficiency of heat recovery	[ % ]	75
Maximum flow rate	[ m <sup>3</sup> /h ]	388
Electric power input of the fan drive at maximum flow rate	[ W ]	168
Sound power level (Lwa)	[ dB(A) ]	46
Reference flow	[ m <sup>3</sup> /s ]	0.08
Reference pressure difference	[ Pa ]	50
SPI	[ W/(m <sup>3</sup> /h) ]	0.28
Control factor and control typology		0.85
Declared maximum internal leakage rates	[ % ]	3.00
Declared maximum external leakage rates	[ % ]	2.56
Position and description of visual filter warning for RVU's		Timer
AEC average	[ kWh ]	250
AEC cold	[ kWh ]	250
AEC warm	[ kWh ]	250
AHS Average	[ kWh/a ]	4220
AHS Cold	[ kWh/a ]	8260
AHS Warm	[ kWh/a ]	1910
Internet address for disassembly instructions		www.salda.lt

