

Specific energy consumption (SEC) cold	[ kWh/m <sup>2</sup> a ]	-74.3
Specific energy consumption (SEC) average	[ kWh/m <sup>2</sup> a ]	-34.5
Specific energy consumption (SEC) warm	[ kWh/m <sup>2</sup> a ]	-11.6
Declared typology		bidirectional
Type of drive installed (fan)		Variable
Type of heat recovery system		regenerative
Thermal efficiency of heat recovery	[ % ]	73
Maximum flow rate	[ m <sup>3</sup> /h ]	735
Electric power input of the fan drive at maximum flow rate	[ W ]	343
Sound power level (Lwa)	[ dB(A) ]	48
Reference flow	[ m <sup>3</sup> /s ]	0.14
Reference pressure difference	[ Pa ]	50
SPI	[ W/(m <sup>3</sup> /h) ]	0.32
Control factor and control typology		0.85
Declared maximum internal leakage rates	[ % ]	3.00
Declared maximum external leakage rates	[ % ]	1.96
Position and description of visual filter warning for RVU's		Timer
AEC average	[ kWh ]	290
AEC cold	[ kWh ]	290
AEC warm	[ kWh ]	290
AHS Average	[ kWh/a ]	4170
AHS Cold	[ kWh/a ]	8160
AHS Warm	[ kWh/a ]	1890
Internet address for disassembly instructions		www.salda.lt

