

Reflex Refix DE 25, diaphragm expansion vessel without through flow, blue, 16/4 bar, stainless steel connection



Article number: 7304015



Features

Type	DE 25
Nominal volume	25 l
Max. useful volume	18,7 l
Max. permissible system temperature	70 °C
Max. perm. operating temperature	70 °C
Max. perm. operating pressure	16 bar
Factory provided gas supply pressure	4 bar
Connection	G 3/4"
Diameter	280 mm
Height	518 mm
Tilt dimension approx.	589 mm
Weight	5,00 kg

Description

Refix DE

Non-flowed through diaphragm expansion tank for water supply installations that are not subject to DIN 1988, e.g. fire extinguishing and service water systems, underfloor heating or heat source installations. Vessels fitted according to DIN EN 13831. Approval according to Pressure Equipment Directive 2014/68/EC.

- Bladder according to DIN EN 13831 / replaceable from 50 litres
- For antifreeze additive of at least 25 – 50 %
- Parts in contact with water are corrosion-protected
- Durable epoxy resin coating
- 33 litres with brackets, from 50 litres with adjustable feet
- From Ø 1,000 mm including pressure gauge
- Pressure gauge and supply pressure valve protected by clip

Note:

No licence requirement according to SWKI HE301-01 and SVTI for (PSV * VN ≤ 3,000 bar * litre).

