

Reflex Reflex G 1000/1000, upright diaphragm expansion vessel, grey, 6/3,5 bar

Article number: 8524605

reflex

Thinking solutions.



Features

| Type | G 1000/1000 |
|--------------------------------------|-------------|
| Nominal volume | 1000 l |
| Max. useful volume | 900 l |
| Max. permissible system temperature | 120 °C |
| Max. perm. operating temperature | 70 °C |
| Max. perm. operating pressure | 6 bar |
| Factory provided gas supply pressure | 3,5 bar |
| Connection | DN65/PN6 |
| Diameter | 1000 mm |
| Height | 1973 mm |
| High water connection | 307 mm |
| Tilt dimension approx. | 1995 mm |
| Weight | 228,00 kg |

Description

Reflex G

Diaphragm expansion tank for sealed heating and cooling water systems. Built according to DIN EN 13831 and VDI 4708 or AD 2000. Approval according to Pressure Equipment Directive 2014/68/EC.

- Durable epoxy resin coating
- Replaceable bladder according to DIN EN 13831
- For antifreeze additive of at least 25 – 50 %
- Pressure gauge and supply pressure valve protected by clip
- Upright configuration
- Max. permissible system temperature 120°C
- Max. operating temperature 70°C
- Connections:
 - up to 1,000 l / Ø 740 mm with threaded connections
 - From 1,000 l / Ø 1,000 mm with flange connections DN65/PN6 or DN65/PN16
- From 1,000 litres and Ø 1,000 mm with MBM coupling
- With inspection opening (from 1,000 litres with Ø 1,000 mm)

