Reflexomat Basic vessel, RG 3000, grey, 10 bar, for Reflexomat press. unit Article-No.:8651505

Reflex Reflexomat Basic Vessel RG, expansion vessel with replaceable bladder equipped for the installation of a 'reflexomat' control unit, for closed heating and cooling systems, built acc. to EN 13831, approval acc. to EU Pressure Equipment Directive 97/23/EC.

Vessel manufactured of steel with red anti corrosion paint protection. In order to prevent interior corrosion due to the presence of condensed water, the vessel is provided on the inside with an epoxy coating with a minimum thickness of 70mµ.

The high quality butyl bladder is preventing the vessel contents from permeation of oxygen.

Vessel supplied with expansion joint,

safety relief valve, level transducer (tank volume).

Vessels stand vertical with steel profile or tubular feet

Type: RG 3000

Merkmale

Nominal volume: 3000 l Useful volume max.: 2700 l perm. flow temp supp. inst.: 120 °C perm. op. temp. diaphragm: 70 °C perm. op. overpressure: 10 bar SV set pressure exp. vessel: 10 bar Diameter: 1500 mm Height: 2532 mm Net weight: 954 kg System connection: DN 65/PN 16 Colour: grau



Reflex Winkelmann GmbH

Gersteinstraße 19 • 59227 Ahlen, Germany • Postfach 2261 • 59210 Ahlen, Germany • Tel.: + 49 2382 7069-0 • Fax: + 49 2382 7069-588 • www.reflex.de Geschäftsführer: Norbert Hülsmann, Volker Mauel

USt.-Ident-Nr.: DE 178 726 058 • Steuer-Nr.: 304/5987/2077 • Handelsregister: Amtsgericht Münster • HRB 13297, Sitz: Ahlen

reflex