Reflexomat Secondary vessel, RF 5000, grey, 6 bar, for Reflexomat press. unit

Article-No.:8652705

Reflex Reflexomat Secondary Vessel RF, expansion vessel with replaceable bladder as additional vessel without control unit for 'reflexomat'compressorcontrolled pressurization unit.

For closed heating and cooling systems, built acc. to EN 13831, approval acc. to EU Pressure Equipment Directive 97/23/EC.

Vessel manufactured of steel with red anti corrosion paint protection. In order to prevent interior corrosion due to the presence of condensed water, the vessel is provided on the inside with an epoxy coating with a minimum thickness of 70mµ.

The high quality of butyl bladder is preventing the vessel contents from permeation of oxygen.

safety relief valve, pneumatic flexible/ regid pipework for interconnection.

Vessels stand vertical with steel profile or tubular feet.

Merkmale

Type: RF 5000 Nominal volume: 5000 l Useful volume max.: 4500 l perm. flow temp supp. inst.: 120 °C perm. op. temp. diaphragm: 70 °C perm. op. overpressure: 6 bar

SV set pressure exp. vessel: 6 bar

Diameter: 1500 mm Height: 3588 mm Net weight: 1115 kg

System connection: DN 65/PN 6

Colour: grau



Gersteinstraße 19 · 59227 Ahlen, Germany · Postfach 2261 · 59210 Ahlen, Germany · Tel.: + 49 2382 7069-0 · Fax: + 49 2382 7069-588 · www.reflex.de Geschäftsführer: Norbert Hülsmann, Volker Mauel

USt.-Ident-Nr.: DE 178 726 058 • Steuer-Nr.: 304/5987/2077 • Handelsregister: Amtsgericht Münster • HRB 13297, Sitz: Ahlen