
Reflexomat Basic vessel RG 350, grey, 10 bar, for Reflexomat press. unit

Article-No.:8654000



Vessel manufactured of steel with red anti corrosion paint protection. In order to prevent interior corrosion due to the presence of condensed water, the vessel is provided on the inside with an epoxy coating with a minimum thickness of 70mµ.

The high quality butyl bladder is preventing the vessel contents from permeation of oxygen.

Vessel supplied with expansion joint,



safety relief valve, level transducer (tank volume).

Vessels stand vertical with steel profile or tubular feet

Merkmale

Type: RG 350 Nominal volume: 350 l Useful volume max.: 315 l perm. flow temp supp. inst.: 120 °C

perm. op. temp. diaphragm: 70 °C perm. op. overpressure: 10 bar SV set pressure exp. vessel: 10 bar

Diameter: 750 mm Height: 1340 mm Net weight: 230 kg

System connection: DN 40/PN 16

Colour: grau



Gersteinstraße 19 • 59227 Ahlen, Germany • Postfach 2261 • 59210 Ahlen, Germany • Tel.: + 49 2382 7069-0 • Fax: + 49 2382 7069-588 • www.reflex.de Geschäftsführer: Norbert Hülsmann, Volker Mauel

USt.-Ident-Nr.: DE 178 726 058 • Steuer-Nr.: 304/5987/2077 • Handelsregister: Amtsgericht Münster • HRB 13297, Sitz: Ahlen