

Reflex Exdirt D 1 1/2, threaded dirt separator, 110 °C, 10 bar

Article-No.:9252040

reflex

Reflex Exdirt, dirt and sludge separator for heating and cooling systems respectively for sealed system circuits.

Suitable for use with water and water/glycol mixture to a maximum of 50% concentration.

Fitting for the removal of dirt particles up to a size of 5,0 µm out of the liquid flow by way of a specifically designated insert.

The collection area can be easily emptied at regular intervals using a drain ball valve while the system remains in operation. The flanged collection chamber can be removed for inspection.

Merkmale

Type: D 1 1/2
Housing material: Messing
Installation model: horizontal
Connection type: Gewinde
System connection: IG 1 1/2
Drain connection: G 3/4
max. operating pressure: 10 bar
max. operating temperature: 110 °C
max. flow: 5 m³/h
kvs: 40 m³/h
Length: 88 mm
Height: 197 mm
Diameter: 65 mm
Weight: 1,5 kg



Reflex Winkelmann GmbH

Gersteinstraße 19 • 59227 Ahlen, Germany • Postfach 2261 • 59210 Ahlen, Germany • Tel.: + 49 2382 7069-0 • Fax: + 49 2382 7069-588 • www.reflex.de
Geschäftsführer: Norbert Hülsmann, Volker Mauel
USt.-Ident-Nr.: DE 178 726 058 • Steuer-Nr.: 304/5987/2077 • Handelsregister: Amtsgericht Münster • HRB 13297, Sitz: Ahlen