

Measurement ranges (also ± measurement ranges) others available upon request	10/50/100/250/500 Pa 1/2.5/5/10/20/50/100 kPa freely scalable from 10..100 % within a measurement range
Margin of error (0.3 Pa margin of error for reference)	±0.2 % or ±0.5 % of the scaled range (40..100 % of max. value) (min. 0.3 Pa)
Temperature coefficient span	0.03 % of max. value/K (10..50 °C)
Temperature coefficient zero point	±0 % (cyclical zero-point correction)
Max. system pressure/ Overload capacity	600 kPa for measurement ranges ≥ 2.5 kPa 200 x for measurement ranges < 2.5 kPa
Medium	air, all non-aggressive gases
Sensor response time	25 ms
Time constants	25 ms..40 s (adjustable)
Operating temperature	10..50 °C
Storage temperature	-10..70 °C
Power consumption	approx. 6 VA
Weight	approx. 750 g
Cable glands	3 x M16
Pressure ports	for tubing NW 6 mm, others available on request
Protection class	IP65, with USB: IP40
Certificates	CE, CSA

Output (linear/ root-extracted) ¹⁾	A
0..10 V (R _L ≥ 2 kΩ)	1
0..20 mA (R _L ≤ 500 Ω)	0
4..20 mA (R _L ≤ 500 Ω)	4
±5 V (R _L ≥ 2 kΩ)	5

Power supply	B
24 VAC/DC ± 10 %	24ACDC
24 VAC + 6 % (with galvanic separation)	24AC
230/115 VAC - 15 %	230/115

¹⁾ output signals can be configured freely

Measurement range	C
Measurement range e.g. 0..10 Pa, -10..50 mbar, ± 100 mmHg (etc.)	

Margin of error	D
±0.2 % ²⁾	2
±0.5 % ²⁾	S

²⁾ of the scaled range (40..100 % of max. value) (min. 0.3 Pa)

Display + keyboard	E
none	0
multi-coloured LCD and keyboard	LC



Contact points	F
none	0
air meter	1
2 relays (changeover contacts) max. 230 VAC, 6 A	2

Data interface	G
none	0
USB (data cable supplied)	U0
External zero-point calibration	0X
External zero-point calibration and USB (data cable supplied)	UX

Order code	A	B	C	D	E	F	G
P26	-	-	-	-	-	-	-

Can be pre-set on request:
Time constant, relay parameter, analogue output root-extracted / linear, deactivation of the cyclic zeroing




Features

- High precision differential pressure transmitter for top-hat rail or wall mounting (air-conditioning, cleanroom, process)
- Wide range of units available for pressure and volume flow, also ± measurement ranges
- Scalable measurement ranges and units
- Zero-point correction prevents zero-point drift
- Built-in valve provides a high level of overpressure protection
- Multilingual menu (English/French/German/Italian)

Optional









- Contact points with adjustable switching outputs
- Set the zero-point via the interface
- USB interface (free parameterisation software at www.halstrup-walcher.com)
- Air meter function



MEASUREMENT OF DIFFERENTIAL PRESSURE

Measurement of differential pressure is useful in a broad range of applications. It is used in ventilation and air-conditioning technology but also in many areas of air handling process technology. The next pages show a number of these. You can find more information about pressure sensor technology on p. 6.

halstrup-walcher offers a wide range of products for stationary measurement of differential pressure.

	PUC24	PUC28(K)	P26	P34	P29	PU/PI/PIZ	PS27	REG21
Details on	p. 18	p. 19	p. 20	p. 21	p. 22	p. 23	p. 24	p. 25
								
Application	Process monitoring for clean-rooms (Pa, °C, % rH), with stainless steel front	Process monitoring panel (optional: with calibration port) (Pa, °C, % rH), aluminium, anodised	High precision, scalable differential pressure transmitter	Measuring transmitter with very small dimensions – ideal for the control cabinet	Like P26, for natural gas	For standard applications. PIZ: PI in two wire technology	A basic sensor for simple applications	Measurement and regulation of pressure
Housing installation	Installed in wall (panel)		Mounted on a wall/top-hat rail					Rack
Max. measurement range	± 250 Pa		± 100 kPa					
Min. measurement range	± 100 Pa		± 10 Pa		± 250 Pa		± 50 Pa	
Degree of measurement uncertainty	0.5 % ¹⁾ (standard)		0.2 % of the scaled range (40..100 % of max. value) ²⁾ (optional) 0.5 % of the scaled range (40..100 % of max. value) ²⁾ (standard)		0.2 % ¹⁾ (optional) 0.5 % ¹⁾ (standard)		0.2 % ^{1) 3)} 0.5 % ^{1) 2)} 1 % ¹⁾ 2 % (≥ 100 Pa) or 3 % (for 50 Pa) of the set value	
Square-root (volume flow)	-	-	✓	✓ ⁴⁾	✓	-	-	-
Display	✓	✓	optional	-	optional	optional	optional	✓

¹⁾ max. value of upper range value

²⁾ but not less than 0.3 Pa

³⁾ for measurement ranges ≥ 250 Pa only

⁴⁾ optionally with stat. pressure sensor and temperature analogue input for compensation

ACCESSORIES

Certificates (see p. 41)

DAkKS calibration certificate (German)

DAkKS calibration certificate (English)

ISO factory calibration certificate

Order no.

9601.0003

9601.0004

9601.0002

Connecting components

Silicone tubing ID 5 mm, OD 9 mm, red 9601.0160
(please state length required)

Silicone tubing ID 5 mm, OD 9 mm, blue 9601.0161
(please state length required)

Norprene tubing 9061.0132
(please state length required)

Y-piece for tubing 9601.0171

Pressure ports

We can supply a wide range of customer-specific pressure ports, e.g. various cutting ring couplings or hose connectors.

